


Fusion & Fusion Shimmer — Ultrafabrics




389-6516 Chroma*




500-3721 Portobello




389-5854 Icicle*




500-5771 Steam



389-3637 Copperhead*




500-9442 Rose Tint



389-6514 Silverado*




500-6513 Dime




389-6515 Tin*




389-8255 Brushed Bronze*



500-3457 Chambord



389-2707 Frost*



500-5721 Caviar




500-5621 Graphite



389-5690 Gunmetal*




389-9350 Plumberry*



500-2736 Deep Midnight

*Fusion Shimmer



Application

Interior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface
65% Recycled Polyester, 35% Rayon Backing

Width:

54 Inches / 137 Centimetres

Repeat:

None

Performance

Abrasion:

ASTM D4157 / 1500,000-250,000 Double Rubs
(Wyzenbeek)*

BS EN ISO 12947-2 / 150,000-180,000 Rubs
(Martindale)*

*meets or exceeds

Hydrolysis:

14 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability)
ISO 1419 Method C (Accelerated Ageing)

Colorfastness

Light: AATCC 16.3, 200 Hours, Grade 4
ISO 105 B02, Grade 6

Crocking: AATCC 8, Grade 4-5 Wet & Dry

Environmental

No intentionally added PFAS

SCS Indoor Advantage certified

REACH compliant

Does not contain any Red List chemicals



Fusion



Fusion Shimmer

Scan QR code
for a full list of
specifications.

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.



ultrafabricsinc.com

Ultrafabrics® and logo are registered trademarks of Ultrafabrics Inc. Made in Japan.

