Outdoor Living — Ultrafabrics

To brave the outdoors you'll need a solution that stands up to the elements. Our Outdoor Living materials repel water and withstand fading to provide lasting beauty. Engineered with an EPA-registered defense against mildew, Outdoor Living represents comfort and protection combined.



Featured Collections —

Residential: Brisa Forecast | Brisa Frontier | Coast | Pumice | Summit

Marine:

Above Deck — Coast | Pumice
Below Deck — All other collections

Contract: Coast | Pumice

- Superior durability industry-leading 16 weeks hydrolysis results
- Premium, 100% polycarbonate construction withstands harsh cleaners and disinfectants
- Coast, Summit and Pumice features an EPA-registered antimicrobial agent that inhibits the growth of bacteria and other microbes.
- Enhanced UV colorfastness
- Stays cool to the touch

Live outside the box.









Outdoor Living

Application

Interior Upholstery, Exterior Upholstery

General Specifications

Composition:

100% Polycarbonate Polyurethane Surface 65% Recycled Polyester, 35% Rayon Backing[†]

Weiaht:

Approx. 10.9 - 11.5 oz. Per Square Yard Approx. 370 - 390 Grams Per Square Metre

Thickness:

Approx. 1.05 - 1.15 Millimetres

Width:

54 Inches / 137 Centimetres

Repeat:

8"V x 10.5"H / 203mm V x 267mm H (Brisa Frontier & Summit)

Performance

Abrasion:

ASTM D4157 / 200,000 - 400,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 100,000 - 200,000 Rubs (Martindale)* *meets or exceeds

Hydrolysis:

Breaking Strength:

16 Weeks

ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)

Adhesion of Coating: ASTM D751

Tear Strength: **ASTM D2261** ASTM D751

Seam Strength: ASTM D751 (Tack Tear)

Tensile Strength: BS EN ISO 1421

Cold Crack: FTM 5874 / CFFA 6a

Air Permeability*: ASTM D737

Antibacterial**: AATCC 147

Antimicrobial**: **ASTM E2180**

Antimildew: ASTM G21

Colorfastness

UV: ASTM G154, 1000 Hours Light: AATCC 16.3, 200 Hours, Grade 4

> SAE J2527 1500 kj, Grade 4** ISO 105 B02, Grade 6-8

Crocking: AATCC 8, Grade 4-5 Wet & Dry Chlorinated Water: AATCC 162, Class 4-5

Perspiration: AATCC 15, Class 5 Sea (Salt) Water: AATCC 106, Class 4-5

Flammability Requirements

- · ASTM E84 (Adhered) Class A
- CA TB 117 Pass
- NFPA 260 Class 1
- UFAC Class 1
- AB 2998

These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform under the fire test conditions of:

ASTM E84 (Unadhered)

• BS EN 1021 Parts 1 & 2

• BS 5852 Source 0.1 & 5

• IMO FTPC Part 8

(Cig, Match & Crib 5)

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

*Only pertains to Brisa Forecast & Brisa Frontier

**Only pertains to Coast, Pumice & Summit

†Only pertains to Brisa Frontier & Summit



